

MODIFICATIONS TO CLAIM STATUS

In complete response to the Examiner's Requirement for Restriction, dated 12/10/2004, the Applicant hereby elects Group I including claims 1—35 and 38—61, without traverse.

In accordance with the PTO's revised Response format, a detailed listing of all claims has been provided. This listing of claims will replace all prior versions, and listings, of claims in the application.

By way of overview, claims 1—61 are currently pending. Of these pending claims:

- A) Claims 1—61 remain in their original form; and
- B) Claims 36 and 37 are currently withdrawn.

Listing of Claims

1. (Original.) A method comprising:
identifying a target service to which access is sought on behalf of a client;
causing a server operatively coupled to the client to request access to the target service on behalf of the client, from a trusted third-party, wherein the server provides the trusted third-party with a credential authenticating the server, information about the target service, and a service credential previously provided by the client to the server.

2. (Original.) The method as recited in Claim 1, wherein the trusted third-party includes at least one service selected from a group of services

1 comprising a key distribution center (KDC) service, a certificate granting authority
2 service, and a domain controller service.

3
4 3. (Original.) The method as recited in Claim 2, wherein the trusted
5 third-party provides the server with a new service credential granted in the name
6 of the client rather than the server.

7
8 4. (Original.) The method as recited in Claim 3, wherein the new
9 service credential is configured for use by the server and the target service to
10 which access is sought.

11
12 5. (Original.) The method as recited in Claim 3, wherein the credential
13 authenticating the server is a ticket that includes a ticket granting ticket associated
14 with the server.

15
16 6. (Original.) The method as recited in Claim 1, further comprising:
17 causing the trusted third-party to verify that the client has authorized
18 delegation.

19
20 7. (Original.) The method as recited in Claim 6, wherein:
21 the trusted third-party includes a key distribution center (KDC); and
22 causing the trusted third-party to verify that the client has authorized
23 delegation includes verifying the status of a restriction placed on the ticket
24 originating from the client.

1
2 8. (Original.) The method as recited in Claim 1, further comprising:
3 causing the trusted-third-party to selectively determine if the client is
4 allowed to participate in delegation either based on information selected from a
5 group comprising an identity of the client, a group affiliation associated with the
6 client.

7
8 9. (Original.) The method as recited in Claim 1, wherein the server is a
9 front-end server with respect to a back-end server that is coupled to the front-end
10 server, and wherein the back-end server is configured to provide the target service
11 to which access is sought.

12
13 10. (Original.) The method as recited in Claim 1, wherein:
14 the trusted third-party includes a key distribution center (KDC);
15 the KDC provides a ticket-granting-ticket associated with the client to the
16 client; and
17 the client does not provide the ticket granting ticket to the server.

18
19 11. (Original.) The method as recited in Claim 1, wherein:
20 the trusted third-party includes a key distribution center (KDC); and
21 the server requests the new credential in a ticket granting service request
22 message that includes a service ticket provided by the client to the server.

23
24 12. (Original.) A method comprising:
25

1 identifying a target service to which access is sought on behalf of a client;
2 and

3 causing a server operatively coupled to the client to request access to the
4 target service on behalf of the client, from a trusted third party, wherein the server
5 provides the trusted third party with a service credential authenticating the server,
6 information about the target service, and a service credential previously provided
7 by the client for the service, and wherein the client ticket includes implementation-
8 specific identity information.

9
10 13. (Original.) The method as recited in Claim 12, wherein the
11 implementation-specific identity information includes information selected from a
12 group comprising privilege attribute certificate (PAC) information, security
13 identifier information, Unix identifier information, Passport identifier information,
14 certificate information.

15
16 14. (Original.) The method as recited in Claim 13, wherein the PAC
17 information includes compound identity information.

18
19 15. (Original.) The method as recited in Claim 13, wherein the PAC
20 information includes access control restrictions for use as delegation constraints.

21
22 16. (Original.) A computer-readable medium having computer-
23 executable instructions for performing tasks comprising:

1 in a server, determining a target service to which access is sought on behalf
2 of a client coupled to the server;

3 requesting a new service credential from a trusted third-party by providing
4 the trusted third-party with a credential authenticating the server, information
5 about the target service, and a service credential associated with the client and the
6 requesting server.

7
8 17. (Original.) The computer-readable medium as recited in Claim 16,
9 wherein the trusted third-party includes at least one service selected from a group
10 of services comprising a key distribution center (KDC) service, a certificate
11 granting authority service, and a domain controller service.

12
13 18. (Original.) The computer-readable medium as recited in Claim 17,
14 wherein the new service credential is granted in the name of the client rather than
15 the server.

16
17 19. (Original.) The computer-readable medium as recited in Claim 18,
18 wherein the service credential is configured for use by the server and the target
19 service.

20
21 20. (Original.) The computer-readable medium as recited in Claim 18,
22 wherein the credential authenticating the server includes a ticket granting ticket
23 associated with the server.

1 21. (Original.) The computer-readable medium as recited in Claim 16,
2 further comprising:

3 causing the trusted third-party to verify that the client has authorized
4 delegation.

5
6 22. (Original.) The computer-readable medium as recited in Claim 21,
7 wherein:

8 the trusted third-party includes a key distribution center (KDC); and

9 causing the trusted third-party to verify that the client has authorized
10 delegation includes verifying the status of a forwardable flag value as set by the
11 client..

12
13 23. (Original.) The computer-readable medium as recited in Claim 16,
14 wherein the server is a front-end server with respect to a back-end server coupled
15 to the front-end server, and wherein the back-end server is configured to provide
16 the target service.

17
18 24. (Original.) The computer-readable medium as recited in Claim 16,
19 wherein:

20 the trusted third-party includes a key distribution center (KDC);

21 the KDC provides a ticket-granting-ticket associated with the client to the
22 client; and

23 the client does not provide the ticket granting ticket to the server.
24
25

1 25. (Original.) The computer-readable medium as recited in Claim 16,
2 wherein:

3 the trusted third-party includes a key distribution center (KDC); and
4 the requesting server requests the new service credential in a ticket granting
5 service request message that includes a service ticket provided by the client to the
6 server.

7
8 26. (Original.) A system comprising:
9 a credential granting mechanism configured to receive a request for a new
10 service credential from a server and in response generate the new service
11 credential if delegation is allowable, and wherein the request includes:

12 a credential authenticating the requesting server,
13 identifying information about a target service to which access is sought on
14 behalf of a client coupled to the server, and
15 a service credential that was previously granted to the client for use with the
16 server.

17
18 27. (Original.) The system as recited in Claim 26, wherein the
19 credential granting mechanism is provided by a trusted third party and includes at
20 least one service selected from a group of services comprising a key distribution
21 center (KDC) service, a certificate granting authority service, and a domain
22 controller service.

1 28. (Original.) The system as recited in Claim 27, wherein the new
2 service credential is granted in the name of the client rather than the server.

3
4 29. (Original.) The system as recited in Claim 28, wherein the service
5 credential is configured for use by the server and the target service.

6
7 30. (Original.) The system as recited in Claim 28, wherein the
8 credential authenticating the server includes a ticket granting ticket associated with
9 the server, and which was previously granted by the credential granting
10 mechanism.

11
12 31. (Original.) A system comprising:
13 a server configured to generate a request for a new service credential from a
14 trusted third-party, the new service credential being associated with a client and a
15 target service, the request comprising:

16 a credential authenticating the server,
17 information about the target service, and
18 a service credential associated with the client and the server.

19
20 32. (Original.) The system as recited in Claim 31, wherein the trusted
21 third-party includes at least one service selected from a group of services
22 comprising a key distribution center (KDC) service, a certificate granting authority
23 service, and a domain controller service.

1 33. (Original.) The system as recited in Claim 31, wherein the
2 credential authenticating the server includes a ticket granting ticket associated with
3 the server.

4
5 34. (Original.) The system as recited in Claim 31, wherein the server is
6 a front-end server with respect to the service.

7
8 35. (Original.) The system as recited in Claim 31, wherein the server
9 requests the new service credential in a ticket granting service request message
10 that includes the service ticket associated with the client and the server.

11
12 36. (Withdrawn.) A computer-readable medium having stored thereon a
13 data structure, comprising:

14 a credential authenticating a first server,
15 information identifying a second server, and
16 a service credential associated with a client and the first server.

17
18 37. (Withdrawn.) The computer-readable medium as recited in Claim
19 36, wherein the credential authenticating the first server includes a ticket-granting-
20 ticket (TGT) and the service credential includes a service ticket.

21
22 38. (Original.) A method comprising:
23 separately authenticating a server and a client;
24 providing the server with a server ticket granting ticket;
25

1 providing the client with a client ticket granting ticket and a service ticket
2 for use with the server;

3 providing the server with a new service ticket for use by the server for use
4 with a new service without requiring the server to have access to the client ticket
5 granting ticket.

6
7 39. (Original.) The method as recited in Claim 38, further comprising:
8 causing the server to request the new service ticket on behalf of the client
9 by forwarding the server ticket granting ticket, information identifying the new
10 service, and the service ticket to a trusted third party.

11
12 40. (Original.) A method comprising:
13 identifying a target service to which access is sought on behalf of a client
14 that has been authenticated using a first authentication method;
15 causing a server that is operatively coupled to the target service and the
16 client to request a service credential to itself from a second authentication method
17 trusted third-party by identifying the client and the first authentication protocol;
18 and

19 causing the server to request a new service credential , for use by the server
20 and the target service, from the second authentication method trusted third-party,
21 wherein the server provides the trusted third-party with a credential authenticating
22 the server, information about the target service, and the service credential to itself.

1 41. (Original.) The method as recited in Claim 40, wherein the second
2 authentication method trusted third-party includes at least one service selected
3 from a group of services comprising a key distribution center (KDC) service, a
4 certificate granting authority service, and a domain controller service.

5
6 42. (Original.) The method as recited in Claim 41, wherein the new
7 service credential is granted in an identity of the client rather than an identity of
8 the server.

9
10 43. (Original.) The method as recited in Claim 42, wherein the service
11 credential is configured for use by the server and the target service to which access
12 is sought.

13
14 44. (Original.) The method as recited in Claim 42, wherein the
15 credential authenticating the server includes a ticket granting ticket associated with
16 the server.

17
18 45. (Original.) The method as recited in Claim 40, further comprising:
19 upon receiving a request for the new service credential from the server,
20 causing the second authentication method trusted third-party to verify that the
21 client has authorized delegation.

1 46. (Original.) The method as recited in Claim 40, wherein the server is
2 a front-end server with respect to a back-end server that is coupled to the front-end
3 server, and wherein the back-end server is configured to provide the target service.

4
5 47. (Original.) The method as recited in Claim 40, wherein the first
6 authentication method is selected from a group of authentication methods
7 comprising Passport, SSL, NTLM, and Digest.

8
9 48. (Original.) The method as recited in Claim 40, wherein the second
10 authentication method includes a Kerberos authentication protocol.

11
12 49. (Original.) A computer-readable medium having computer-
13 executable instructions for performing tasks comprising:

14 identifying a target service to which access is sought on behalf of a client
15 that has been authenticated using a first authentication method;

16 causing a server that is operatively coupled to the target service and the
17 client to request a service ticket to itself from a second authentication method
18 trusted third-party by identifying the client and the first authentication protocol;
19 and

20 causing the server to request a new service ticket, for use by the server and
21 the identified service, from the second authentication method trusted third-party,
22 wherein the server provides the trusted third-party with a ticket authenticating the
23 server, information about the target service, and the service ticket to itself.

24

25

1 50. (Original.) The computer-readable medium as recited in Claim 49,
2 wherein the second authentication method trusted third-party includes a key
3 distribution center (KDC).

4
5 51. (Original.) The computer-readable medium as recited in Claim 50,
6 wherein the new service ticket includes a service ticket granted in an identity of
7 the client rather than an identity of the server.

8
9 52. (Original.) The computer-readable medium as recited in Claim 51,
10 wherein the service ticket is configured for use by the server and the target service.

11
12 53. (Original.) The computer-readable medium as recited in Claim 51,
13 wherein the ticket authenticating the server includes a ticket granting ticket
14 associated with the server.

15
16 54. (Original.) The computer-readable medium as recited in Claim 49,
17 further comprising:

18 upon receiving a request for the new service ticket from the server, causing
19 the second authentication method trusted third-party to verify that the client has
20 authorized delegation.

21
22 55. (Original.) The computer-readable medium as recited in Claim 49,
23 wherein the server is a front-end server with respect to a back-end server that is
24
25

1 coupled to the front-end server, and wherein the back-end server is configured to
2 provide the target service.

3
4 56. (Original.) The computer-readable medium as recited in Claim 49,
5 wherein the first authentication method is selected from a group of authentication
6 methods comprising Passport, SSL, NTLM, and Digest.

7
8 57. (Original.) The computer-readable medium as recited in Claim 49,
9 wherein the second authentication method includes a Kerberos authentication
10 protocol.

11
12 58. (Original.) A system comprising:
13 a server configurable to:
14 identify a target service to which access is sought on behalf of a
15 client that has been authenticated using a first authentication method,
16 request a service credential to itself from a second authentication
17 method trusted third-party by identifying the client and the first
18 authentication method, and
19 subsequently request a new service credential, for use by the server
20 and the target service, from the second authentication method trusted third-
21 party,
22 wherein the server provides the second authentication method
23 trusted third-party with a credential authenticating the server, information about
24 the target service, and the service credential to itself.
25

1
2 59. (Original.) The system as recited in Claim 58, wherein the new
3 service credential is granted in an identity of the client rather than the server.
4

5 60. (Original.) The system as recited in Claim 59, wherein the new
6 service credential is configured for use by the server and the target service.
7

8 61. (Original.) The system as recited in Claim 59, wherein the
9 credential authenticating the server includes a ticket granting ticket associated with
10 the server.
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25